AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A dial assembly comprising:

a first member having a pivot pin attached thereto;

a dial magnet rotatably mounted on said pivot pin;

a reed switch assembly positioned operatively adjacent to said dial magnet comprising:

a reed switch; and

a bias magnet positioned such [[as]] that said reed switch is held in the first position when the poles of said dial and bias magnets are in a first orientation and will be held in a second position when the poles of the dial magnet and bias magnet are in a second orientation.

2. (Original) A dial assembly of claim 1 further comprising a cover defining a receptacle for receiving said reed switch assembly.

3. (Original) A dial assembly comprising of claim 1 wherein in said first position of said reed switch the reeds of said reed switch are in contact.

4. (Original) A dial assembly comprising of claim 2 wherein in said first position of said reed switch the reeds of said reed switch are in contact.

5. (Currently Amended) A dial assembly comprising:

a first member having a pivot pin attached thereto;

a dial magnet rotatably mounted on said pivot pin;

a second member attached to said first member to form a cover;

a reed switch assembly removably positioned operatively adjacent to said dial magnet comprising:

a reed switch; and

a bias magnet positioned such [[as]] that said reed switch is held in the first position when the poles of said dial and bias magnets are in a first orientation and will be held in a second position when the poles of the dial magnet and bias magnet are in a second orientation.

6. (Original) A dial assembly of claim 5 further wherein said first member defines a receptacle for receiving said reed switch assembly.

7. (Original) A dial assembly of claim 6 further wherein said second member defines a receptacle for receiving said reed switch assembly.

8. (Original) A dial assembly comprising of claim 5 wherein in said first position of said reed switch the reeds of said reed switch are in contact.

9. (Original) A dial assembly comprising of claim 6 wherein in said first position of said reed switch the reeds of said reed switch are in contact.

10. (Original) A dial assembly comprising of claim 7 wherein in said first position of said reed switch the reeds of said reed switch are in contact.

11. (Currently Amended) A gauge comprising:

(a) a gauge assembly having

(i) a gauge head;

(ii) a support member extending from said gauge head;

(iii) a transmitting shaft having a first end and a second end rotatable in said support member;

(iv) a tank magnet attached to said first end of said transmitting shaft;

(v) a float arm linked to said transmitting shaft such that movement of said float arm results in rotation of said transmitting shaft;

(b) a dial assembly mounted on said gauge assembly having:

(i) a first member having a pivot pin attached thereto;

(ii) a dial magnet rotatably mounted on said pivot pin;

(iii) a reed switch assembly positioned operatively adjacent to said dial magnet comprising:

(iv) a reed switch; and

(v) a bias magnet positioned such [[as]] <u>that</u> said reed switch is held in the first position when the poles of said dial and bias magnets are in a first orientation and will be held in a second position when the poles of the dial magnet and bias magnet are in a second orientation.

12. (Original) A dial assembly of claim 11 further comprising a cover defining a receptacle for receiving said reed switch assembly.

13. (Original) A dial assembly comprising of claim 12 wherein in said first position of said reed switch the reeds of said reed switch are in contact.

14. (Original) A dial assembly comprising of claim 13 wherein in said first position of said reed switch the reeds of said reed switch are in contact.